

BOLA Tri-Clamp Adapters, Bohlender

① BOLA Tri-Clamp GL adapters

Fitting for transition of Tri-Clamp as per DIN 32 676 to a GL-threaded neck. Made of PTFE, temperature resistance -200°C to +250°C, universal chemical resistance.

Plate Ø mm	Nominal size acc. to DIN	for tube inner Ø mm	Thread GL	Order No.
25.5	DN 08	8	14	10 17 60102
25.5	DN 10	10	18	10 17 60104
25.5	DN 10	10	25	10 17 60106
34.0	DN 10	10	14	10 17 60122
34.0	DN 15	16	18	10 17 60124
34.0	DN 20	20	25	10 17 60126
50.5	DN 25	26	14	10 17 60142
50.5	DN 25	26	18	10 17 60144
50.5	DN 32	32	25	10 17 60146
50.5	DN 40	38	45	10 17 60148
91.0	DN 65	66	18	10 17 60172
91.0	DN 65	66	25	10 17 60174
91.0	DN 65	66	45	10 17 60176

BOLA Tri-Clamp multiple distributor

Fitting for transition of Tri-Clamp as per DIN 32 676 to two or three GL-threaded necks. Made of PTFE, temperature resistance -200°C to +250°C, universal chemical resistance.

Plate Ø mm	Nominal size acc. to DIN	for tube inner Ø mm	Thread GL	Bore Ø mm	Order No.
25.5	DN 10	10	2 × 14	2 × 4.5	10 17 61103
② 34.0	DN 20	20	2 × 14	2 × 8.5	10 17 61122
③ 50.5	DN 40	38	3 × 14	3 × 8.5	10 17 61142
50.5	DN 40	38	3 × 18	3 × 10.5	10 17 61144
91.0	DN 65	66	3 × 18	3 × 10.5	10 17 61172

④ BOLA adapter Tri-Clamp hose connector

Fitting for transition of Tri-Clamp as per DIN 32 676 to a hose connector. Made of PTFE, temperature resistance -200°C to +250°C, universal chemical resistance.

Plate Ø mm	Nominal size acc. to DIN	for tube inner Ø mm	Tube connector outer Ø mm	Order No.
25.5	DN 08	8	10.4	10 17 61502
34.0	DN 10	10	10.4	10 17 61522
50.5	DN 25	26	16.0	10 17 61542

⑤ BOLA Tri-Clamp gaskets

Silicone ring with double-sided, elastic washer made of PTFE. Suitable for Tri-Clamp connections as per DIN 32 676. Universal chemical resistance, the flowing product is only exposed to PTFE. Temperature resistance -60°C to +230°C, universal chemical resistance.

Plate Ø mm	Nominal size acc. to DIN	for tube inner Ø mm	Order No.
25.5	DN 08	8	10 17 63002
25.5	DN 10	10	10 17 63004
34.0	DN 10	10	10 17 63022
34.0	DN 15	16	10 17 63024
34.0	DN 20	20	10 17 63026
50.5	DN 25	26	10 17 63042
50.5	DN 32	32	10 17 63044
50.5	DN 40	38	10 17 63046
64.0	DN 50	50	10 17 63062
91.0	DN 65	66	10 17 63072

