

Graduated Cylinders, PP, Class B, VITLAB

① Graduated cylinders with embossed blue graduations

Highly transparent. With easily readable, raised, embossed blue scale and ring mark at the primary scale points. Calibrated „In“. Class B tolerances according to DIN 12681/ISO 6706.

Hexagonal base with bottom studs provides high stability. Thermal stress up to 80°C does not cause tolerance limits to be permanently exceeded. To preserve markings, do not clean at temperatures exceeding 60°C.

Suitable for contact with foodstuffs according to ordinance (EU) No. 10/2011.

Vol. ml	Tol. ± ml	Grad. ml	Height mm	Ø mm	Order No.	PU pc/Pack
10	0.2	0.20	145	15	23 85 10159	12
25	0.5	0.50	170	22	23 85 10168	12
50	1.0	1.00	200	27	23 85 10175	12
100	1.0	1.00	250	33	23 85 10178	12
250	2.0	2.00	315	44	23 85 10184	6
500	5.0	5.00	360	58	23 85 10188	6
1000	10.0	10.00	440	69	23 85 10192	6
2000	20.0	20.00	482	97	23 85 10196	3

② Graduated cylinders with embossed graduations

Highly transparent. With a raised scale and ring mark at the primary scale points calibrated „In“. Class B tolerances according to DIN 12681/ISO 6706.

Hexagonal base with bottom studs provides high stability. Thermal stress up to 80°C does not cause tolerance limits to be permanently exceeded.

Suitable for contact with foodstuffs according to ordinance (EU) No. 10/2011.

Vol. ml	Tol. ± ml	Grad. ml	Height mm	Ø mm	Order No.	PU pc/Pack
10	0.2	0.20	145	15	10 85 31159	12
25	0.5	0.50	170	22	10 85 31168	12
50	1.0	1.00	200	27	10 85 31175	12
100	1.0	1.00	250	33	10 85 31178	12
250	2.0	2.00	315	44	10 85 31184	6
500	5.0	5.00	360	58	10 85 31188	6
1000	10.0	10.00	440	69	10 85 31192	6
2000	20.0	20.00	482	97	10 85 31196	3

