

Liquid Transfer Pumps, BÜRKLE



WWR4Q010



OTAL liquid transfer pumps can be used with any commercially available container. When inserting the hand pump, the telescopic riser pipe adjusts to the container height. This ensures thorough emptying of residues and makes the hand pump fit for use with different containers. The liquid to be transferred comes into contact with the feed pipes only.

- With universal plug made of soft PVC, for container openings 30 – 70 mm Ø
- High capacity
- As a hand pump for containers of up to 60 litres or as a foot pump for containers of up to 120 litres

PP: Resistant to weak acids, lyes, and cleaning agents.

PVDF: For acids and lyes, not for heavily oxydising acids and lyes, resistant to chlorine bleaching

Stainless steel: For flame-resistant liquids of hazard class AIII (VbF) – not for acids.



① OTAL foot pumps

Material	Immersion depth cm	Flow rate l/min	Tubing Ø mm	Order No.
PP	70	20	15	29 05 20115
PP	70	26	18	29 05 20118
PP	90	30	22	29 05 20122
PVC delivery tubing	70	12	12	29 05 20312
PVDF	70	20	16	29 05 24028
Stainless steel	90	26	18	29 05 24228

② OTAL hand pumps

Material	Immersion depth cm	Flow rate l/min	Tubing Ø mm	Order No.
PP	70	14	12	29 05 21112
PP	70	20	15	29 05 21115
PP	70	26	18	29 05 21118
PVDF	70	20	16	29 05 24128
Stainless steel	90	26	18	29 05 24328
PVC delivery tubing	70	12	12	29 05 00812
PP1)	45	4	10	29 05 22100

1) OTAL mini hand pump, for containers up to 10 litres and container openings diam. 20-36 mm.

