

Micro Centrifuges, Eppendorf



WWQJ3039

eppendorf

① Micro centrifuges MiniSpin® and MiniSpin® plus

Product features of the MiniSpin® and MiniSpin® plus centrifuges:

- Exceptionally small footprint
- Extremely quiet
- Maintenance-free drive

Additional product features of the MiniSpin® centrifuge:

- Includes standard rotor made of anodized aluminum
- Max. speed of 13,400 rpm; max. rcf of 12,100 x g

Additional product features of the MiniSpin® plus centrifuge:

- Max. speed of 14,500 rpm; max. rcf 14,100 x g
- rpm/rcf setting as required
- Timer can be set up to 99 minutes
- Continuous centrifugation possible

Article	Order No.
Centrifuge MiniSpin®	55 69 54520
230 V/50-60 Hz, incl. standard rotor, anodized aluminium, 45° angle, 12 bores for 1.5/2 ml reaction tubes with max. Ø 11 mm, complete with stainless steel lid	

Article	Order No.
Centrifuge MiniSpin® plus	55 69 54530
230 V/50-60 Hz, incl. „F-45-12-11“ rotor, in refined black aluminium, 45° angle, 12 bores for 1.5/2 ml reaction tubes with max. Ø 11 mm, complete with stainless steel lid	

Accessories

Article	Order No.
② PCR strip rotor F-55-16-5-PCR	10 69 27007
including rotor cover	
Rotor cover	55 69 02000
Stainless steel with knurled nut	
Adapter	55 69 16001
For 0.5 ml micro centrifuge tube and 0.6 ml Microtainers®, 6 pieces	
Adapter	55 69 17008
For 0.4 ml micro centrifuge tube, 6 pieces	
Adapter	55 69 15005
For 0.2 ml PCR tube, 6 pieces	

BD Microtainer®: registered trademark of Becton Dickinson



①



②

