

Precision Balances BTA Series, Phoenix Instrument

The BTA series is equipped with the UNIBLOC weighing system. It ensures excellent stability, reaction, and reliability features. Thanks to the innovative, compact design of the measuring cells in connection with the digital processing technology, it is possible to achieve extremely short measuring times with high stability.

3 calibration modes:

- Fully automatic calibration after change of temperature
- Fully automatic calibration at times defined by the user
- Calibration at the push of a button

Other features of the BTA series:

- Automatic adaptation to ambient conditions
- Comfortable operation via keys
- Measuring time 3 seconds
- Very easy data transmission via Windows direct function
- Various application programs
- User-defined time intervals for data output
- Die-cast aluminum housing
- Internal calibration
- On request, the balances can be supplied officially calibrated/approved
- Dust cover comprised as a standard
- 5 years warranty



Type	Incram. g	Weigh. range g	Platform mm	Order No.
BTA-623	0.001	620	108×105	10 13 76231
BTA-623V ¹⁾	0.001	620	108×105	10 13 76232
BTA-423	0.001	420	108×105	10 13 74231
BTA-423V ¹⁾	0.001	420	108×105	10 13 74232
BTA-6202	0.01	6200	170×180	10 13 76202
BTA-6202V ¹⁾	0.01	6200	170×180	10 13 76203
BTA-4202	0.01	4200	170×180	10 13 74202
BTA-4202V ¹⁾	0.01	4200	170×180	10 13 74203
BTA-2202	0.01	2200	170×180	10 13 72202
BTA-2202V ¹⁾	0.01	2200	170×180	10 13 72203
BTA-822	0.01	820	170×180	10 13 78221
BTA-822V ¹⁾	0.01	820	170×180	10 13 78222
BTA-8201	0.01	8200	170×180	10 13 78201
BTA-4201	0.01	4200	170×180	10 13 74201

¹⁾ Officially calibratable