

Oxygen Meters, METTLER TOLEDO

① Portable DO meter (dissolved oxygen) Seven2Go S4

Intuitive-operation meter for routine mobile dissolved-oxygen (DO) measuring tasks (IP67) in laboratory, production, and in the field with a wide range of applications:

- extremely easy, intuitive operation, robust and ergonomic design
- large multi-function display: all data at a glance
- ISM® (Intelligent Sensor Management)
- Data logger for 200 data records
- automatic atmospheric pressure compensation
- automatic, time controlled, or manual recording of measured values
- water- and dust-proof (IP67)
- operation via AA or rechargeable batteries

Technical Data:

DO measuring range: 0 to 99 mg/l / resolution 0.01

Air pressure: 500 to 1100 mbar

Temperature range: 0 to 60°C / resolution 0.1°C

Article	Order No.
S4 meter	10 50 02651
Measurement device, electrode clip, battery, certificate	
S4 Standard Kit	10 50 02652
as S4 meter, plus sensor InLab605-ISM, sample bottles	
S4 Field Kit	10 50 02653
as S4-Standard Kit, plus field bag	

② Portable pH/oxygen meter SevenGo Duo pro™ SG98 RDO

- 2-channel handheld meter for measuring pH, mV, ion concentration, and dissolved oxygen
- Unique optical RDO sensor for fast, accurate, and stable O₂ measurements: More robust than LDO sensors, fast reaction, immediately ready for operation, extra-easy handling
- Intelligent sensor management (ISM®) for optimum sensor control and longer useful life
- Full GxP support, easy and safe operation
- 1- or 2-point calibration
- Data memory for 500 GLP data records with date/time of day, sensor ID and SN, user and sample ID
- Wireless IR communication
- Large backlit graphic display

Article	Order No.
SG98-B	10 50 02661
2-channel-meter, 4 batteries, user manual, certification	
SG98-ELK	10 50 02662
as SG98-B, plus O ₂ electrode InLab® OptiOx-ISM, pH electrode InLab® Expert pro-ISM	
SG98-FK2	10 50 02663
as SG98-ELK, plus protective cover, field bag, calibration bottle, sensor accessories	
SG98-FK5	10 50 02664
as SG98-FK2, but with 5 m electrode cable	

③ Accessories

Article	Order No.
RDO sensor InLab®OptiOx-ISM-2m	10 50 04621
incl. 2 m cable, mini-LTW-connector, with 5 m or 10 m cable: have a look at SevenGo Duo ISM sensors	
Replacement cap	10 50 04630
for InLab® OptiOx sensor	
Calibration bottle	10 50 04631
for InLab® OptiOx sensor	
Protective cap/sinker (stainless steel)	10 50 04632
for InLab® OptiOx sensor	
BOD adapter	10 50 04633
for InLab® OptiOx sensor	

More sensors see page XXX.

